

2MP Network PTZ Integrated Explosion proof Camera






FEATURES

- Highest Rated Explosion Proof International Certification (Ex d IIC T6 / IECEx, ATEX, UL)
- Gas: Zone 1 & 2, Group IIC T6
- Dust: Zoon 21 & 22, Group IIIC T85 °C
- Durable SUS316L material
- Optical 30X, Digital 16X Auto Focus Zoom Lens
- 2 Megapixel Full HD, 1080p
- H.265 / H.264 / MJPEG triple codec support
- Supports up to 60fps@1080p transmission and triple streaming
- Up to 100° rotation per second, Pan 360° continuous / Tilt 180° (Auto Flip)
- 250 Preset positions, Tour / Auto pan support
- Automatically tracking PTZ events
- Intelligent monitoring function (separate license)
- Various security policies and hardware built-in security chip
- Wiper, Sunshield Integrated / Washer Jet System Support

DIMENSION

(unit: mm)



SPECIFICATION

MODEL	HEPZ302W0
Sensor	1/2.8" SONY Progressive CMOS
Effective Pixels	1920(H) x 1080(V)
Scanning System	Progressive Scan
Min. Illumination	0.005Lux(Color), 0.0005Lux(B/W)
S/N Ratio	More than 55dB(AGC Off)
Focal Length	f=4.5~135mm(F1.6-F4.4), Optical 30x, Digital 16x
Focus Control	Manual / Auto / Semiauto / PTZ Trigger
Day & Night	Auto(ICR) / Color / BW
WDR	OFF / BLC / HLC / WDR(120dB)
White Balance	Auto / Indoor / Outdoor / ATW / Manual / Outdoor Auto / Sodium Lamp Auto / Sodium Lamp
Electric Shutter	1/1~1/30,000sec
Privacy Mask	OFF / ON(Max. 24 zone Settings)
EIS (Electronic Image Stabilization)	OFF / ON
Defog	OFF / ON
Pan / Tilt Speed	Pan : 360° Endless / Tilt : -90°~+90°(Flip), Preset Speed : 0.1"/sec ~ 100"/sec
Pan / Tilt Mode	250 Preset, Tour, Auto Pan
Auto Tracking	Support
Ethernet	RJ-45 (10/100 Base-T PoE)
Video Codec	H.265, H.264, MJPEG
Video Streaming	Main : 60fps@1080p, 30fps@1.3MP/720p 2nd : 30fps@1080p/1.3MP/720p 3rd : 30fps@D1/CIF
Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, SSL, ICMP, FTP, SMTP, DHCP, PPPoE, UPNP, IGMP, SNMP, Bonjour, DNS, DDNS, IEEE 802.1x, QoS, NTP, IP Filter, ONVIF, RS-485 Pelco P/D
Security	Multiple user access levels with enhanced password policy, IP Filtering, IEEE 802.1x, Strong Digest authentication for Access permission, HTTPS, TLS1.2 only; high strength encrypted algorithm AES-256, SSH/Telnet closed and FTP disabled to reduce surface being attacked, PCI-DSS compliant, built-in cybersecurity hardware chipset
ONVIF	ONVIF Profile S, Q
Max. user access	Max. 20 users
Xtralis Mode	Xtralis intelligent function compatible (separate line sense), Roaming detection, Intrusion detection function
Standard Mode	Motion detection, Face detection
Operating Temp.	-40°C ~ +60°C
Operating Hum.	10%~90% RH, non-condensing
Power	AC24V/5A, Max. 120W
Certification type	UL, CE, KCs, ATEX, IECEx
Certification Class	IECEx Ex d IIC T6 Gb Ta / Ex tb IIIC T85°C Db Ta ATEX II2 G Ex d IIC T6 Gb Ta / II 2 D Ex tb IIIC T85°C Db Ta UL Class 1, Zone 1, Aex d IIC T6 / Zone 21, Aex tb IIIC T85°C
Protection grade	IP66
Material	SUS316L Stainless Steel Construction
Dimension (mm)	336(W) x 398(H) x 232(D)
Weight	Approx. 27.5Kg
Accessories	Washerjet, Wall Bracket, Plane Bracket, Pole Mount Adaptor, Conner Mount adaptor, External Cable

* Specification and design are subject to change without notice.