

H.265 PC Type Full HD NVR





FEATURES

- Reliable and Stable Operation based on **Linux 64bit**
- Prompt & Stable operation with **DOM SSD**
- High Quality Full HD Video of H.265, H.264 Compression
- ONVIF / RTSP standard protocol support
- Various Recording Mode
; Continuous, Motion, Sensor, Schedule Mode
- Event Pop-up for Motion/Sensor/Camera loss/Etc.,
- Selectable Streaming Mode and Quality
; Recording/Streaming/Quality
- 2 way Audio Supported
- Multi User Authorization & Screen Lock Function
- E-map Monitoring(VMS)
- Failover Support
- Various Client Program Provided
- User-friendly design and GUI
- Max. 70TB Recording Capacity (7HDD Bay)

DIMENSION

(unit : mm)



SPECIFICATION

MODEL	MV-N36	MV-N49	MV-N64	
DISPLAY				
Video	Channel	36 CH	49 CH	64 CH
	Output	1 x VGA / 1 x HDMI (or 1 x DVI)		
Display	Resolution	Full HD(1080P) : 1920 x 1080		
	Speed	1080fps	1470fps	1920fps
RECORDING				
Compression	H.265, H.264, MPEG-4, MJPEG			
Resolution	Full HD(1080p) 1920 x 1080			
Speed	1080fps	1470fps	1920fps	
Recording Mode	Continuous, Motion Detection, Sensor, Schedule, Event			
Pre/Post Alarm	Pre Alarm : 10sec / Post Alarm : Max 120sec			
SEARCH				
Mode	Date/Time, Calendar, Event			
Playback	Forward (Fast : x1 ~ x8, Slow : 1/4 ~ 1/2) Step Forward/Backward			
NETWORK				
Interface	10/100/1000 BASE-T RJ-45 Gigabit Ethernet			
Protocol	TCP/IP, UDP, DNS, DDNS, HTTP, NTP, RTP/RTCP, RTSP			
3 rd party IP Camera Protocol	ONVIF / RTSP Supported Camera, UDP, Axis, Dynacolor, SONY, Panasonic, SAMSUNG, etc.,			
Max. User	1024			
Bandwidth Control	Auto			
CMS Software	Live, Search, Back-up, Event Manager, E-Map, Multi Monitor, PAN/TILT/Zoom Control, NVR Set-up			
Web Client (IE only)	Live 100CH, PAN/TILT/ZOOM Control			
Mobile APP	iPhone / Android APP			
Security	3 User Level			
Alarm	FTP Notice via e-mail, Alarm Out, Programmed Preset, Event & Video Loss Warning, Popup Camera			
Failover	Supported			
STORAGE				
Internal Space	7 HDD Bay (Up to 70TB, 3.5inch)			
External Storage	eSATA, iSCSI Support			
RAID	Normal, Option - RAID5, RAID6			
SYSTEM & GENERAL				
System	CPU	Intel Core Processor 3.5GHz		
	RAM	DDR3 32G		
	OS	Embedded Linux 64bit (DOM-SSD 32G)		
KVM Switch Interface	USB Only (+PS/2 Type is Unavailable)			
External equipment interlocking (Option)	Elevator CRT system interlocking(Korea products only), Emergency bell, LPR system, Fire/Smoke detection system (H/W & S/W)			
Power Consumption	AC100~240V 50/60Hz			
Power Source	Max. 600W			
Operating Temp./HR	5°C ~ 40°C / 0~90%			
Case Type	4U Rack Mount			
Dimension	441.4(W) x 173.96(H) x 454(D)			
Weight	Approx. 18.5Kg (exclude HDD)			

* Specification and design are subject to change without notice.