
Hybrid LED Landscape Lighting





Applicable range : Parks, trails, trails, hazardous area safety signs, deck facilities, stepping stones, golf courses, landscaping facilities, etc.

Specification

Item	Туре	Use environment	Model NO
LED Landscape Lighting	Hybrid Type	Average sunshine (less than 3.5 hours)	MK-70HL
	Solar Type	Average sunshine (more than 3.5 hours)	MK-70SL

ltem	Spec.		ltem	Spec.
Lighting device	Super Luminosity LED x 6ea		Relief day	Hybrid Model : 365 day, Solar Model : 3 day
Controller	· Ultra Low Power MCU Controller		Main material	Polycarbonate, AL Casting
Power supply Solar Model	Solar Cell : 4V/150mA/Hr	Protection standard	IP67	
	,	Battery 1 : Li-FePO4 3.2V / 1500mA	Dimension (mm)	W127mm x D127mm x H60mm (Inner diameter W100 x D100 x H42)
		Battery 2 : Lithium 3.6V / 7.2A	life span	5 to 10 years (depending on the amount of sunshine)
	Color	Solar Cell : 4V/150mA/Hr	Weight	500g
		Battery 1 : Li-FePO4 3.2V / 1500mA		

Features

- Visibility of more than 500m using high-brightness LED
- Shock resistance, waterproof (IP67), dustproof construction
- Internal module and protective cap separation structure facilitates maintenance
- Hybrid power structure and power control technology applied 365 days a year. (Hybrid Model)
- RF ON/OFF Control (Option)

MONE S&C